



TECHNICAL DATA SHEET
ID Product Code 251MEW3G010
Rev. 01/2020

PRIMER 3G

Product based on resins in a watery dispersion specially formulated to strengthen flaking or crumbly subfloors

Application

STRENGTHENING AND ANTI-DUST TREATMENT Prepare the surfaces to be treated by removing all traces of material that may act as a separating agent (oils, greases, paints, dust, etc.). PRIMER 3G must be diluted, according to the absorbency of the subfloor, in the following ratio: 1 part PRIMER 3G and 1 or 2 parts water. Apply this solution with a roller or brush to the amount of 100- 250 g/m² . If necessary, apply another coat of product after 2 and within 12 hours. Before proceeding with the subsequent laying phase, wait at least 2-3 days. This interval may be considerably longer according to particular morphological conditions of the screed and environmental factors. Therefore, the degree of moisture in the screed must be checked using a carbide hygrometer before continuing with the gluing. Only use Bellinzoni vinyl adhesives. If a film forms on the surface, some sand must be scattered on the primer while still fresh. Once the primer has dried, the excess sand must be removed. **ADHESION IMPROVER FOR CEMENT LEVELLING** Prepare the surfaces to be treated by removing all traces of material that may act as a separating agent (oils, greases, paints, dust, etc.). Apply one coat of pure PRIMER 3G and then apply the cement levelling product (with LEVEL MAX).

Suggestion for use and recommendations

Do not apply the product below 10°C or above 30°C. Store above freezing. Product subject to the restrictions prescribed by EC Dir.2004/42. Product for professional use



Chemical characteristics

Average coverage per coat (g/m ²)	100/250
Max permitted dilution (EC Dir.2004/42)	Only water
Calculated VOC (g/ltr)	10
To clean tools	Water
Release of dangerous substances	See MSDS
Shelf life	12 Months in original, unopened containers stored in cool, dry.place)
At 20°C (indicative values not constituting product specifications)	

Safety procedures

As far as the proper working procedures is concerned, we recommend to consult Material Safety Data Sheets issued according to E.U. rules and to follow your national laws concerning safety in the working place. MSDS is available on our web site www.primaxbuild.it

Trademark and Origin of the good

PRIMAX[®] is a registered trademark of Bellinzoni company. The law considers a trademark to be a form of property and any misuse can be persecuted by law. Bellinzoni s.r.l. declares that our product PRIMER 3Gis MADE IN ITALY.

DISCLAIMER All data indicated in this leaflet are the results of tests and experiments carried out in our laboratories and through reliable operators in the stone business and have to be considered reliable. Because of the many factors which can influence them, the information here reported do not constitute implicit or formal guarantees. The end user undertakes the responsibility in the usage of the product making sure to experiment the product characteristic as preventive measure.



Application surfaces
Concrete surface



Application tools
Brush, Roll.



Coverage
100/250 per g/m² .



Storage
12 months from production date in its original packaging (unopened container) between 5° and 30° C in a cool dry place.



Packing
Buckets 10/ 25 lt.