

# BITUPAINT ALU

**RESINOUS ALUMINIUM PAINT** 

Specific paint for bituminous coating

BITUPAINT ALU is a protective silver colored paint very compatible for bituminous coating (BITU-MAX VULCANO).

## Mixing and application

BITUPAINT ALU is can be applied on every type of dried surfaces; its specific application is as a protective coat on bituminous membranes to give pleasant look.

Product is ready for use. Stir the product before application and apply using a brush or a roll.







TECHNICAL DATA SHEET ID Product Code 262 Rev. 01/2020

#### Recommendations

Do not apply BITUPAINT when weather is bad or if rain, fog or temperature under + C are expected. These conditions should be ensured for at least 12 hours after application. Previde for suitable slopes of the concrete in arder to avoid prolonged water stagnation over the BITUPAINT film. Keep the cans at  $+5^{\circ}$  C.

#### Chemical characteristics

| Chemical properties                          | Water bassed paint  |
|--|---|
| Colour                                       | Bright aluminium  |
| Dry bulk density                             | 0,98 ± 0,02   |
| Dry time                                     | At surface: 30 min at 20°C – In depth 2 hours at 20°C   |
| U.V. resistance                              | Very good   |
| Resisance to foot traffic                    | Good  |
| Allowed dilution                             | Ready for use   |
| Leed   | approved  |
| Release of dangerous substances              | See MSDS  |
| Shelf life                                   | 12 months from production date in its original packaging (unopened container) between 5° and 30° C in a cool dry place. |
| * indicative values, depending on the nature | e of the material and environmental conditions  |



#### Coverage 1 kg for 10-15 m2



### Storage

12 months in original intact packaging and stored in a dry place.



Packing
Drums of 10 kg and 20 kg

#### Safety procedures

As far as the proper working procedures is concerned, we recommend to consult Material Safety Data Sheets issued according to E.U. rules and to follow your national laws concerning safety in the working place. MSDS is available on our web site www.primaxbuild.it

# Trademark and Origin of the good

PRIMAX® is a registered trademark of Bellinzoni company. The law considers a trademark to be a form of property and any misuse can be persecuted by law. Bellinzoni s.r.l. declares that our product BITUPAINT is MADE IN ITALY.

DISCLAIMER All data indicated in this leaflet are the results of tests and experiments carried out in our laboratories and through reliable operators in the stone business and have to be considered reliable. Because of the many factors which can influence them, the information here reported do not constitute implicit or formal guarantees. The end user undertakes the responsibility in the usage of the product making sure to experiment the product characteristic as preventive measure



